

Product information

Digital Micrometers Micromar 40 EWR

Product features

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbide-tipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission via connection cable), Data interface Bi-Directional (external output and input option of characteristic values as well as setting of individual lock functions by software MarCom)

Package contains

setting values, battery, test certificate, instruction manual, case




Item no.: 4157015

Technical data

Measuring range mm	0 - 100 mm
Measuring range	0 - 4"
Resolution mm/inch	0.001 / .00005"
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	carbide
Spindle diameter	6.5
Spindle thread pitch_mm	0.5

Dimensions



Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Interface adapter with data cable Digimatic	DK-D1