

# Product information

## Digital Micrometer Micromar 40 EWR-L

### Product features

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbide-tipped
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

### Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission via connection cable), Data interface Bi-Directional (external output and input option of characteristic values as well as setting of individual lock functions by software MarCom)

### Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

### Application

- Avoiding workpiece damage: The non-rotating spindle has a touching touch, which prevents scratch marks on sensitive and finely machined surfaces
- Ideal for measuring thin metal foils without twisting and bending them
- Thread flank measurement by using thread wires: Both wire holders always remain in the engaged position with the non-rotating spindle




Item no.: **4157023**

### Technical data

<b>Measuring range mm</b>	75 - 100 mm
<b>Measuring range</b>	3 - 4"
<b>Resolution mm/inch</b>	0.001 / .00005"
<b>Error limit <math>\mu\text{m}</math></b>	3
<b>Parallel error in <math>\mu\text{m}</math></b>	3
<b>Flatness in <math>\mu\text{m}</math></b>	0.6
<b>Measuring force (N)</b>	5 - 10
<b>Battery type</b>	CR 2032 (3V Lithium)
<b>Material Contact surface</b>	carbide
<b>Spindle diameter</b>	6.5
<b>Spindle thread pitch_mm</b>	5

### Dimensions

<b>Dimensions b in mm</b>	13
<b>Dimensions a in mm</b>	57
<b>Dimensions c in mm</b>	107



### Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Interface adapter with data cable Digimatic	DK-D1