

## Product information

## Digital micrometer Micromar 40 EWR-K

## Product features

- **Measuring surfaces: Anvil with narrow web, pointed spindle**
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbide-tipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



## Functions

RESET (set display to zero),  
ABS (display can be set to zero  
without losing reference to  
ORIGIN), mm/inch, ORIGIN (for  
entering a numerical value),  
LOCK function (key lock), TOL  
(Tolerance and Warning Limits  
Input), HOLD (freeze current  
measured value), DATA (data  
transmission), Bi-directional  
data interface (for data retrieval,  
transfer of parameters, remote  
control, individual function locks  
via MarCom software)

Item no.: **4157040**

## Technical data

Measuring range mm	0 - 20 mm
Measuring range	0 - 0.8"
Resolution mm/inch	0.001 / .00005"
Error limit µm	4
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	carbide
Spindle diameter	6.5
Spindle thread pitch_mm	0.5

### Package contains


battery, test certificate,  
instruction manual, case

## Application

For measuring crimp heights on crimp contacts and end splices

## Dimensions

Dimensions b in mm	9.5
Dimensions a in mm	23
Dimensions c in mm	31.5



## Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Interface adapter with data cable Digimatic	DK-D1