

Product information

Digital micrometer Micromar 40 EWR-V

Product features

- With mounting bores for measuring anvils with a shaft $\varnothing 3.5$ mm
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

Item no.: 4157048

Technical data

| | |
|---------------------------|----------------------|
| Measuring range mm | 75 - 100 mm |
| Measuring range | 3 - 4" |
| Resolution mm/inch | 0.001 / .00005" |
| Error limit μm | 5 |
| Measuring force (N) | 5 - 10 |
| Battery type | CR 2032 (3V Lithium) |
| Spindle diameter | 6.5 |
| Spindle thread pitch_mm | 5 |

Package contains


battery, test certificate, instruction manual, case

Application

For measuring thread flanks and gear diameters using quick-change measuring anvils.

Dimensions

| | |
|--------------------|-------|
| Dimensions b in mm | 17 |
| Dimensions a in mm | 73 |
| Dimensions c in mm | 132.5 |



Accessories

| Order no. | Designation | Product type |
|-----------|---|--------------|
| 4102603 | Data cable USB bidirectional | DK-U1 |
| 4102606 | Interface adapter with data cable Digimatic | DK-D1 |