Product information

Digital Micrometer Micromar 40 EWRi

Product features

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbidetipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

Functions

RESET (set display to zero),
ABS (display can be set to zero
without losing reference to
ORIGIN), mm/inch, ORIGIN (for
entering a numerical value),
LOCK function (key lock),
TOL (Tolerance and Warning
Limits Input), HOLD (storage of
measured values), DATA (data
transmission), Bi-directional data
interface (external output and
input option of characteristic
values as well as setting of
individual lock functions by
software MarCom)

Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

Data interface

Integrated Wireless

Energy supply

Battery life approx. 3 years (approx. 0.5 in wireless mode)




Item no.: **4157102**

Technical data

Battery type	CR 2032 (3V Lithium)
Measuring range mm	50 - 75 mm
Measuring range inch	2 - 3"
Material Contact surface	carbide
Resolution mm/inch	0.001 / .00005"
Error limit µm	3
Parallel error in µm	3
Flatness in µm	0.6
Spindle diameter	6.5
Spindle thread pitch_mm	0.5
Measuring force (N)	5-10

Dimensions

Dimensions b in mm	13
Dimensions a in mm	45
Dimensions c in mm	82



Accessories

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick