# **Product information**

# **Digital Micrometer Micromar 40 EWRi**

#### **Product features**

- · High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbidetipped
- · Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

#### **Functions**

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

## Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case




Item no.: 4157106

### **Technical data**

Measuring range mm	150 - 175 mm
Measuring range	6 - 7"
Resolution mm/inch	0.001 / .00005"
Error limit µm	4 μm
Parallel error in µm	4 μm
Flatness in µm	0.6 μm
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	carbide
Spindle diameter	6.5 mm
Spindle thread pitch_mm	0.5 mm

### **Dimensions**

Dimensions b in mm	13 mm
Dimensions a in mm	95 mm
Dimensions c in mm	182 mm



### **Accessories**

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick