Product information

Digital micrometer Micromar 40 EWRi-B

Product features

- **Reduced measuring surfaces** Ø 3 mm
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbidetipped
- Rapid drive
- Ratchet is integrated in the thimble
- · Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

Package contains

setting standard (measuring range of 25-50 mm), battery, test Dimensions certificate, instruction manual, case

Application

For measuring grooves, spline shafts, recesses, etc.




Item no.: 4157132

Technical data

Measuring range mm	0 - 25 mm	
Measuring range	0 - 1"	
Resolution mm/inch	0.001 / .00005"	
Error limit µm	4	
Measuring force (N)	5 - 10	
Battery type	CR 2032 (3V Lithium)	
Material Contact surface	carbide	
Spindle diameter	6.5	
Spindle thread pitch_mm	0.5	

Dimensions b in mm	11.5
Dimensions a in mm	32
Dimensions c in mm	57



Accessories

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick