Product information

Digital micrometer Micromar 40 EWRi-B

Product features

· Reduced measuring surfaces Ø 3 mm

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- · Spindle and anvil are carbidetipped
- Rapid drive
- Ratchet is integrated in the thimble
- · Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval - transfer of parameters - remote control - individual function locks via MarCom software)

Package contains

setting standard (measuring range of 25-50 mm), battery, test Dimensions certificate, instruction manual, case

Application

For measuring grooves, spline shafts, recesses, etc.




Item no.: 4157133

Technical data

Measuring range mm	25 - 50 mm		
Measuring range	1 - 2"		
Resolution mm/inch	0.001 / .00005"		
Error limit µm	4 µm		
Measuring force (N)	5 - 10		
Battery type	CR 2032 (3V Lithium)		
Material Contact surface	carbide		
Spindle diameter	6.5 mm		
Spindle thread pitch_mm	0.5 mm		

Dimensions b in mm	13.5 mm
Dimensions a in mm	44 mm
Dimensions c in mm	82 mm



Accessories

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick