Product information

Digital micrometer Micromar 40 EWRi-K

Product features

Measuring surfaces: Anvil with narrow web, pointed spindle

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbidetipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

Package contains

battery, test certificate, instruction manual, case

Application

For measuring crimp heights




Item no.: 4157140

Technical data

Measuring range mm	0 - 20 mm
Measuring range	0 - 0.8"
Resolution mm/inch	0.001 / .00005"
Error limit µm	4 µm
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	carbide
Spindle diameter	6.5 mm
Spindle thread pitch_mm	0.5 mm

Dimensions

Dimensions b in mm	9.5 mm	40 EWR(i)-K
Dimensions a in mm	23 mm	<u>9</u> .
Dimensions c in mm	31.5 mm	4



Accessories

Order no.	Designation	Product type	9	
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick		