Product information

Digital micrometer Micromar 40 EWRi-S

Product features

- With blade-type measuring surfaces
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

Application

For measuring recesses, grooves, etc.




Item no.: 4157143

Technical data

| Measuring range mm | 50 - 75 mm |
|--------------------------|----------------------|
| Measuring range | 2 - 3" |
| Resolution mm/inch | 0.001 / .00005" |
| Error limit µm | 5 |
| Measuring force (N) | 5 - 10 |
| Battery type | CR 2032 (3V Lithium) |
| Material Contact surface | hardened steel |
| Spindle diameter | 6.5 |
| Spindle thread pitch_mm | 5 |

Dimensions

Dimensions b in mm15.5Dimensions a in mm57Dimensions c in mm107



Accessories

| Order no. |
|-----------|
| 4102220 |