

Product information

Digital Micrometers Micromar 40 EWRI-L

Product features

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbide-tipped
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



Functions

RESET (set display to zero),
ABS (display can be set to zero
without losing reference to
ORIGIN), mm/inch, ORIGIN (for
entering a numerical value),
LOCK function (key lock), TOL
(Tolerance and Warning Limits
Input), HOLD (freeze current
measured value), DATA (data
transmission), Bi-directional
data interface (for data retrieval,
transfer of parameters, remote
control, individual function locks
via MarCom software)

Item no.: **4157410**


Technical data

Measuring range mm	0 - 100 mm
Measuring range	0 - 4"
Resolution mm/inch	0.001 / .00005"
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	carbide
Spindle diameter	6.5
Spindle thread pitch_mm	5

Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

Dimensions



Application

- Avoiding workpiece damage: The non-rotating spindle has a touching touch, which prevents scratch marks on sensitive and finely machined surfaces
- Ideal for measuring thin metal foils without twisting and bending them
- Thread flank measurement by using thread wires: Both wire holders always remain in the engaged position with the non-rotating spindle

Accessories

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick