Product information

Digital Micrometers Micromar 40 EWRi-L

Product features

- · High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbidetipped
- QUICK DRIVE
- · Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



RESET (set display to zero),
ABS (display can be set to zero
without losing reference to
ORIGIN), mm/inch, ORIGIN (for
entering a numerical value),
LOCK function (key lock),
TOL (Tolerance and Warning
Limits Input), HOLD (storage of
measured values), DATA (data
transmission), Bi-directional data
interface (external output and
input option of characteristic
values as well as setting of
individual lock functions by
software MarCom)

Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

Application

- Avoiding workpiece damage: The non-rotating spindle has a touching touch, which prevents scratch marks on sensitive and finely machined surfaces
- Ideal for measuring thin metal foils without twisting and bending them
- Thread flank measurement by using thread wires: Both wire holders always remain in the engaged position with the nonrotating spindle

Data interface

Integrated Wireless

Energy supply

Battery life approx. 2 years (approx. 0.5 in wireless mode)




Item no.: 4157410

Technical data

Battery type	CR 2032 (3V Lithium)		
Measuring range mm	0 - 100 mm		
Measuring range inch	0 - 4"		
Material Contact surface	carbide		
Resolution mm/inch	0.001 / .00005"		
Spindle diameter	6.5		
Spindle thread pitch_mm	5		
Measuring force (N)	5 - 10		

Dimensions



Accessories

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick