

Product information

3-point inside micrometer Micromar 44 A

Product features

- Operating and display units with satin chrome finish
- Stainless spindle is hardened throughout and ground
- Rapid drive with integrated ratchet
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium



Item no.: 4190017

Technical data

| | |
|---|------------------------------------|
| Measuring range mm | 175 - 200 mm |
| Graduation value mm | 0,005 |
| Error limit μm | 7 μm |
| Notes error limit | over the full length of the anvils |
| Spindle thread pitch_mm | 0.5 mm |

Package contains

instruction manual, allen key, key for replacing measuring heads (from 30 mm), case

Application

- For measuring:
- Through holes
 - Blind holes
 - Centering shoulders

Dimensions

| | |
|---------------------------|--------|
| Dimensions b in mm | 27 mm |
| Dimensions c in mm | 7 mm |
| Dimensions d in mm | 132 mm |



Accessories

| Order no. | Designation | Product type |
|-----------|--------------|--------------|
| 4710122 | Setting ring | 355 E |