

Product information

3-point inside micrometer Micromar 44 A

Product features

- Operating and display units with satin chrome finish
- Stainless spindle is hardened throughout and ground
- Rapid drive with integrated ratchet
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium



Item no.: 4190319

Technical data

| | |
|---------------------------------------------|------------------------------------|
| Measuring range mm | 40 - 50 mm |
| Graduation value mm | 0,005 |
| Error limit μm | 4 μm |
| Notes error limit | over the full length of the anvils |
| Spindle thread pitch_mm | 0.5 mm |

Package contains

instruction manual, allen key, key for replacing measuring heads (from 30 mm), case

Application

- For measuring:
- Through holes
 - Blind holes
 - Centering shoulders

Dimensions

| | |
|---------------------------|-------|
| Dimensions b in mm | 15 mm |
| Dimensions c in mm | 5 mm |
| Dimensions d in mm | 76 mm |



Accessories

| Order no. | Designation | Product type |
|-----------|--------------|--------------|
| 4710060 | Setting ring | 355 E |