

Product information

Measuring pistol Micromar 844 A

Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with a rotatable display

Item no.: **4487614**



Package contains

excludes indicator, basic units 844 Ag, measuring head 44 Ak, instruction manual, case

Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:


- through holes
- blind holes
- centering shoulders

Technical data

| | |
|---|---|
| Measuring range mm | 100 - 125 mm |
| Measuring range | 4 - 4.9" |
| Error limit μm | 5 μm |
| Notes error limit | •Over the full length of the anvils •Indicator is not taken into consideration |

Dimensions

| | |
|---------------------------|--------|
| Dimensions b in mm | 27 mm |
| Dimensions c in mm | 7 mm |
| Dimensions d in mm | 132 mm |



Accessories

| Order no. | Designation | Product type |
|-----------|--------------|--------------|
| 4710121 | Setting ring | 355 E |