Product information

Measuring pistol Micromar 844 A

Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with ltem no.: 4487700 a rotatable display



Technical data

Package contains

excludes indicator, basic units 844 Ag, measuring head 44 Ak, instruction manual, case

Application


Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:

- · through holes
- blind holes
- · centering shoulders

Measuring range mm	6 - 8 mm		
Measuring range	.253125"		
Error limit µm	3 μm		
Notes error limit	3 · · · · · · · · · · · · · · · · · · ·		
	 Indicator is not taken into consideration 		

Dimensions

Dimensions b in mm	4 mm
Dimensions a in mm	1.5 mm
Dimensions c in mm	1.5 mm
Dimensions d in mm	58 mm



Accessories

Order no.	Designation	Product type
4710026	Setting ring	355 E
4102915	Data cable Digimatic	16 EWd
4102410	Data connection cable RS232C	16 EXr
4102357	Data connection cable USB	16 EXu
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick