

Product information

Measuring pistol Micromar 844 A

Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Anvils from 12 mm are carbide tipped
- From 12 mm the anvils can be used to measure the bottom of a bore
- From 40 mm all measuring heads are made from aluminium to reduce weight
- Measuring value indication is always easy to read when using an electronic dial indicator with a rotatable display



Item no.: **4487700**

Technical data

Measuring range mm	6 - 8 mm
Measuring range	.25 - .3125"
Error limit µm	3
Notes error limit	•Over the full length of the anvils •Indicator is not taken into consideration

Package contains

excludes indicator, basic units 844 Ag, measuring head 44 Ak, instruction manual, case


Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:

- through holes
- blind holes
- centering shoulders

Dimensions

Dimensions b in mm	4
Dimensions a in mm	1.5
Dimensions c in mm	1.5
Dimensions d in mm	58



Accessories

Order no.	Designation	Product type
4710026	Setting ring	355 E
4102410	Data connection cable RS232C	16 EXr
4102357	Data connection cable USB	16 EXu
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick