# **Product information**

# Measuring pistol Micromar 844 A

#### Product features

- · Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with Item no.: 4487701 a rotatable display

#### Package contains

excludes indicator, basic units 844 Ag, measuring head 44 Ak, instruction manual, case

#### Application

- Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:
- through holes
- blind holes
- · centering shoulders




## **Technical data**

Measuring range mm	8 - 10 mm		
Measuring range	.31254"		
Error limit µm	3 µm		
Notes error limit	<ul><li>Over the full length of the anvils</li><li>Indicator is not taken into consideration</li></ul>		

#### **Dimensions**

Dimensions b in mm	4.3 mm
Dimensions a in mm	1.8 mm
Dimensions c in mm	1.5 mm
Dimensions d in mm	58 mm



### Accessories

Order no.	Designation	Product type
4710026	Setting ring	355 E