Product information

Measuring pistol in set Micromar 844 AS

Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Anvils from 12 mm are carbide tipped
- From 12 mm the anvils can be used to measure the bottom of a bore
- From 40 mm all measuring heads are made from aluminium to reduce weight
- Measuring value indication is always easy to read when using an electronic dial indicator with a rotatable display

Package contains

instruction manual, setting rings, key for replacing measuring heads (from 30 mm), case

Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:

- through holes
- blind holes
- $\boldsymbol{\cdot}$ centering shoulders



Item no.: 4487751

Technical data

| Measuring range mm | 12 - 20 mm |
|--------------------|---|
| Measuring range | .4725775" |
| Error limit µm | 4 |
| Notes error limit | •Over the full length of the anvils |
| | Indicator is not taken into consideration |

Accessories

| Order no. | Designation | Product type |
|-----------|--|--------------|
| 4102357 | Data connection cable USB | 16 EXu |
| 4102410 | Data connection cable RS232C | 16 EXr |
| 4102915 | Interface adapter with data cable Digimatic | 16 EWd |
| 4102231 | Transmitter | 16 EWe |
| 4102230 | Receiver | e-Stick |