

Product information

Measuring pistol in set Micromar 844 AS

Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Anvils from 12 mm are carbide tipped
- From 12 mm the anvils can be used to measure the bottom of a bore
- From 40 mm all measuring heads are made from aluminium to reduce weight
- Measuring value indication is always easy to read when using an electronic dial indicator with a rotatable display



Item no.: **4487761**

Technical data

Measuring range mm	12 - 20 mm
Measuring range	.4725 - .775"
Resolution mm/inch	0.0005 / .00002"
Error limit µm	4
Notes error limit	•Over the full length of the anvils •Indicator is not taken into consideration
Battery type	CR 2450N (3V Lithium)

Package contains

instruction manual, digital Indicator 1086 R, setting rings, key for replacing measuring heads (from 30 mm), case

Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:

- through holes
- blind holes
- centering shoulders

Accessories

Order no.	Designation	Product type
4102357	Data connection cable USB	16 EXu
4102410	Data connection cable RS232C	16 EXr
4102915	Interface adapter with data cable Digimatic	16 EWd
4102231	Transmitter	16 EWe
4102230	Receiver	e-Stick