

# Product information

## Measuring pistol in set Micromar 844 AS

### Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with a rotatable display

Item no.: **4487762**



### Package contains

instruction manual, digital Indicator 1086 R, setting rings, key for replacing measuring heads (from 30 mm), case

### Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:

- through holes
- blind holes
- centering shoulders

### Technical data

<b>Measuring range mm</b>	20 - 50 mm
<b>Measuring range</b>	.775 - 2"
<b>Resolution mm/inch</b>	0.0005 / .00002"
<b>Error limit µm</b>	4 µm
<b>Notes error limit</b>	•Over the full length of the anvils •Indicator is not taken into consideration
<b>Battery type</b>	CR 2450N (3V Lithium)

### Accessories

Order no.	Designation	Product type
4102357	Data connection cable USB	16 EXu
4102410	Data connection cable RS232C	16 EXr
4102915	Data cable Digimatic	16 EWd