

Product information

Compact column measuring instrument Millimar S 1840 PE/M

Product features

- When using pneumatic compact amplifiers, it is recommended at all times to use both a pressure regulator and a supply filter (see accessories)
- Clear, three color analog light bar display of warning and tolerance limits
- Backlit, two line LCD for displaying measured values, help texts and units of measurement
- 1 channel
- RS-232 interface
- Analog output
- 3 digital inputs for measurement start, master measurement, etc.
- 3 digital outputs for good, reject, rework classification, measuring time, etc.
- Dynamic measurements: Max, Min, Max-Min, Max+Min, Average
- Can either be programmed via the integrated membrane keypad using the menu driven interface or via the configuration software for MS Windows®
- 1-point or 2-point master measurement
- Password block in setup mode

Package contains

instruction manual, power source



Item no.: 5318450

Technical data

Display	101 LED elements, 3 color
Scale reading	± 10, 30, 100, 300, 1000, 3000, 10000 µm
Range and text display	7 digit LCD, 14 segments, alphanumeric
Digital display	7 digit LCD, 7 segments
Range of analog display µm	± 3, ± 10, ± 30, ± 100, ± 300, ± 1000, ± 3000, ± 10000, tolerance related
Range of analog display inches	± .0001", ± .0003", ± .001", ± .003", ± .01", ± .03", ± .1", ± .3", tolerance related
Resolution µm	0,1
Tolerance display	Via color change of the analog display
Compatibility	Mahr
Measuring combination	+A, -A
Features	1
Programs	1
Test steps	1
Dynamic functions	Max, Min, Max-Min, (Max+Min)/2, Average
Configuration	PC, keyboard
Zero setter	electrical
Error limit	0.5 - 1%
Error limit, digital display	+/- 1 place
Error limit, analog display	1% (101 LEDs)
Data interface	RS-232C, wireless
Hardware interfaces	RS-232C, I/O interface
Control inputs	3 optocoupler inputs, 24 V, 10 mA
Control outputs	3 optocoupler outputs, 24 V, 100 mA
Analog output	1 V/mm
Energy supply	Power source, 230 V/115 V; 50/60 Hz
Power consumption	20 VA
IP protection category	IP 43
Relative humidity non-condensing	80
Operating temperature Min	0
Operating temperature Max	45
Temperature coefficient	0.005
Product weight	1.60

Dimensions

Height (mm)	487
--------------------	-----

Product information

Compact column measuring instrument Millimar S 1840 PE/M

Dimensions

Depth (mm)	144
Width (mm)	47

Accessories

Order no.	Designation	Product type
7024634	Data connection cable RS232C	
4102331	Adapter cable RS-232-USB	Millimar - USB
4102233	Transmitter	RS-232 e
4102230	Receiver	e-Stick