

Product information

Compact column measuring instrument Millimar S 1840 PE/F

Product features

- When using pneumatic compact amplifiers, it is recommended at all times to use both a pressure regulator and a supply filter (see accessories)
- Clear, three color analog light bar display of warning and tolerance limits
- Backlit, two line LCD for displaying measured values, help texts and units of measurement
- 1 channel
- RS-232 interface
- Analog output
- 3 digital inputs for measurement start, master measurement, etc.
- 3 digital outputs for good, reject, rework classification, measuring time, etc.
- Dynamic measurements: Max, Min, Max-Min, Max+Min, Average
- Can either be programmed via the integrated membrane keypad using the menu driven interface or via the configuration software for MS Windows®
- 1-point or 2-point master measurement
- Password block in setup mode



Item no.: **5318456**

Technical data

Package contains

instruction manual, power source

| | |
|---|---|
| Energy supply | Power source, 230 V/115 V; 50/60 Hz |
| Range of analog display µm | ± 3, ± 10, ± 30, ± 100, ± 300, ± 1000, ± 3000, ± 10000, tolerance related |
| Resolution µm | 0,1 |
| Display | 101 LED elements, 3 color |
| Digital display | 7 digit LCD, 7 segments |
| Scale reading | ± 10, 30, 100, 300, 1000, 3000, 10000 µm |
| Range and text display | 7 digit LCD, 14 segments, alphanumeric |
| Tolerance display | Via color change of the analog display |
| Compatibility | Federal |
| Measuring combination | +A, -A |
| Features | 1 |
| Programs | 1 |
| Test steps | 1 |
| Dynamic functions | Max, Min, Max-Min, (Max+Min)/2, Average |
| Configuration | PC, keyboard |
| Zero setter | electrical |
| Response time digital display | 0.5 s |
| Response time analog display | 0.5 s |
| Error limit | 0.5 - 1% |
| Error limit, digital display | +/- 1 place |
| Error limit, analog display | 1% (101 LEDs) |
| Data interface | RS-232C, wireless |
| Hardware interfaces | RS-232C, I/O interface |
| Control inputs | 3 optocoupler inputs, 24 V, 10 mA |
| Control outputs | 3 optocoupler outputs, 24 V, 100 mA |
| Analog output | 1 V/mm |
| Power consumption max. | 20 VA |
| IP protection category | IP 43 |
| Relative humidity non-condensing | 80 % |
| Operating temperature from | 0 °C |
| Operating temperature up to | 45 °C |
| Temperature coefficient | 0.005 µm/°C |
| Product weight | 1.60 kg |
| Range of analog display inches | ± .0001", ± .0003", ± .001", ± .003", ± .01", ± .03", ± .1", ± .3", tolerance related |

Product information

Compact column measuring instrument Millimar S 1840 PE/F

Accessories

| Order no. | Designation | Product type |
|-----------|------------------------------|----------------------|
| 7024634 | Data connection cable RS232C | RS232C 0-modem cable |
| 4102331 | Adapter cable RS-232-USB | Millimar - USB |