

# Product information

## Dial indicator MarCator 32I-RC

### Product features

- Unit construction and removable movement save repair/cleaning time and maintenance
- Hardened gears and stainless steel racks provide lasting protection against indicator failure due to shock or wear
- Jeweled bearings resist friction, add to longer indicator life
- Skeletonized, hobbed gears for more sensitive response, superior indicator accuracy with minimal hysteresis error
- Soft tinted dials (green - inch / yellow - metric) minimize eye strain
- Special steel alloy
- Balanced dial hand affords no shift, precise reading
- Controlled rack and pinion mesh eliminates slope for precise response and reading
- Smooth adjusting bezels for easy setup
- Positive pressure pull back spring requires less maintenance
- Compliance with ANSI/AGD dimensional and accuracy specifications
- These indicators are normally furnished with continuous dial (with R.C.) or + on right balance dial (w/o R.C.), lug back and .18" by .250" long contact
- Optional Dials: balanced dial with + on left; continuous clockwise; continuous counterclockwise. (Order by part number and specify dial style desired)
- For other dial styles or special requirements - call Mahr



Item no.: **2011051**

### Technical data

<b>Measuring range in inch</b>	0.03
--------------------------------	------

### Dimensions

<b>Dimension B in inches (text)</b>	2.125"
<b>Dimension A in inches (text)</b>	2.75"
<b>Dimension D in inches (text)</b>	.625"
<b>Dimension C in inches (text)</b>	2.563"
<b>Dimension E in inches (text)</b>	.344"

