

Product information

Digital Micrometer Micromar 40 EWR

Product features

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbide-tipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (storage of measured values), DATA (data transmission via connection cable), Bi-directional data interface (external output and input option of characteristic values as well as setting of individual lock functions by software MarCom)

Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

Data interface

MarConnect (bidirectional), USB, Digimatic

Energy supply

Battery life approx. 2 years




Item no.: 4157006

Technical data

Battery type	CR 2032 (3V Lithium)
Measuring range mm	150 - 175 mm
Measuring range inch	6 - 7"
Material Contact surface	carbide
Resolution mm/inch	0.001 / .00005"
Error limit μm	7
Parallel error in μm	4
Flatness in μm	0.6
Spindle diameter	6.5
Spindle thread pitch mm	0.5
Measuring force (N)	5 - 10

Dimensions

Dimensions b in mm	13
Dimensions a in mm	95
Dimensions c in mm	182



Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Interface adapter with data cable Digimatic	DK-D1