

# Product information

## Digital micrometer Micromar 40 EWR-B

### Product features

- **Reduced measuring surfaces**  
**Ø 3 mm**
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbide-tipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



### Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

### Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

### Application

For measuring grooves, spline shafts, recesses, etc.


Item no.: **4157033**

### Technical data

<b>Measuring range mm</b>	25 - 50 mm
<b>Measuring range</b>	1 - 2"
<b>Resolution mm/inch</b>	0.001 / .00005"
<b>Error limit µm</b>	4
<b>Measuring force (N)</b>	5 - 10
<b>Battery type</b>	CR 2032 (3V Lithium)
<b>Material Contact surface</b>	carbide
<b>Spindle diameter</b>	6.5
<b>Spindle thread pitch_mm</b>	0.5

### Dimensions

<b>Dimensions b in mm</b>	13.5
<b>Dimensions a in mm</b>	44
<b>Dimensions c in mm</b>	82



### Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Interface adapter with data cable Digimatic	DK-D1