

Product information

Digital micrometer Micromar 40 EWR-V

Product features

- With mounting bores for measuring anvils with a shaft $\varnothing 3.5$ mm
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval - transfer of parameters - remote control - individual function locks via MarCom software)

Package contains

battery, test certificate, instruction manual, case

Application

For measuring thread flanks and gear diameters using quick-change measuring anvils.




Item no.: 4157047

Technical data

Measuring range mm	50 - 75 mm
Measuring range	2 - 3"
Resolution mm/inch	0.001 / .00005"
Error limit μm	5 μm
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Spindle diameter	6.5 mm
Spindle thread pitch_mm	5 mm

Dimensions

Dimensions b in mm	15.5 mm
Dimensions a in mm	57 mm
Dimensions c in mm	107 mm



Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Data cable Digimatic	DK-D1