

Product information

Digital micrometer Micromar 40 EWR-V

Product features

- With mounting bores for measuring anvils with a shaft $\varnothing 3.5$ mm
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

Item no.: 4157048

Technical data

Measuring range mm	75 - 100 mm
Measuring range	3 - 4"
Resolution mm/inch	0.001 / .00005"
Error limit μm	5
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Spindle diameter	6.5
Spindle thread pitch_mm	5

Package contains


battery, test certificate, instruction manual, case

Application

For measuring thread flanks and gear diameters using quick-change measuring anvils.

Dimensions

Dimensions b in mm	17
Dimensions a in mm	73
Dimensions c in mm	132.5



Accessories

Order no.	Designation	Product type
4102603	Data cable USB bidirectional	DK-U1
4102606	Interface adapter with data cable Digimatic	DK-D1