# **Product information**

# **Digital Micrometer Micromar 40 EWRi**

#### **Product features**

- High contrast digit display
- Stainless spindle is hardened throughout and ground
- Spindle and anvil are carbidetipped
- Rapid drive
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

#### **Functions**

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Data interface Bi-Directional (external output and input option of characteristic values as well as setting of individual lock functions by software MarCom)

### Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case




Item no.: **4157100** 

#### **Technical data**

Measuring range mm	0 - 25 mm
Measuring range	0 - 1"
Resolution mm/inch	0.001 / .00005"
Error limit µm	2
Parallel error in µm	2
Flatness in µm	0.6
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	carbide
Spindle diameter	6.5
Spindle thread pitch_mm	0.5

## **Dimensions**

Dimensions b in mm	9.5
Dimensions a in mm	24
Dimensions c in mm	32



#### **Accessories**

Order no.	Designation Product type
4102220	Wireless i-Stick receiver for measuring instruments with integrated wireless