# **Product information**

## **Digital micrometer Micromar 40 EWRi-S**

#### **Product features**

- · With blade-type measuring surfaces
- · High contrast digit display
- · Stainless spindle is hardened throughout and ground
- · QUICK DRIVE
- · Sliding spindle
- Ratchet is integrated in the thimble
- · Lacquered steel frame, heat insulated



RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Data interface Bi-Directional (external output and input option of characteristic values as well as setting of individual lock functions by software MarCom)

#### Package contains

setting standard (measuring range of 25-50 mm), battery, test **Dimensions** certificate, instruction manual, case

### **Application**

For measuring recesses, grooves, etc.




Item no.: 4157141

#### **Technical data**

Measuring range mm	0 - 25 mm	
Measuring range	0 - 1"	
Resolution mm/inch	0.001 / .00005"	
Error limit µm	4	
Measuring force (N)	5 - 10	
Battery type	CR 2032 (3V Lithium)	
Material Contact surface	hardened steel	
Spindle diameter	6.5	
Spindle thread pitch_mm	5	

Dimensions b in mm	11.5
Dimensions a in mm	32
Dimensions c in mm	57



#### **Accessories**

der no. Designatio
02220 Wireless receiver for measuring instrument with integrated wireless