Product information

Digital micrometer Micromar 40 EWRi-S

Product features

- With blade-type measuring surfaces
- · High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- · Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



RESET (set display to zero),
ABS (display can be set to zero
without losing reference to
ORIGIN), mm/inch, ORIGIN (for
entering a numerical value),
LOCK function (key lock), TOL
(Tolerance and Warning Limits
Input), HOLD (freeze current
measured value), DATA (data
transmission), Bi-directional
data interface (for data retrieval,
transfer of parameters, remote
control, individual function locks
via MarCom software)

Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

Application

For measuring recesses, grooves, etc.




Item no.: **4157142**

Technical data

Measuring range mm	25 - 50 mm
Measuring range	1 - 2"
Resolution mm/inch	0.001 / .00005"
Error limit µm	4
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	hardened steel
Spindle diameter	6.5
Spindle thread pitch_mm	5

Dimensions

Dimensions b in mm	13.5
Dimensions a in mm	44
Dimensions c in mm	82



Accessories

Order no.
4102220