# **Product information**

# **Digital micrometer Micromar 40 EWRi-S**

#### **Product features**

- With blade-type measuring surfaces
- High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated

#### Functions

RESET (set display to zero), ABS (display can be set to zero without losing reference to ORIGIN), mm/inch, ORIGIN (for entering a numerical value), LOCK function (key lock), TOL (Tolerance and Warning Limits Input), HOLD (freeze current measured value), DATA (data transmission), Bi-directional data interface (for data retrieval, transfer of parameters, remote control, individual function locks via MarCom software)

#### Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

#### Application

For measuring recesses, grooves, etc.




Item no.: 4157144

# **Technical data**

Measuring range mm	75 - 100 mm
weasuring range min	75-10011111
Measuring range	3 - 4"
Resolution mm/inch	0.001 / .00005"
Error limit µm	5
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	hardened steel
Spindle diameter	6.5
Spindle thread pitch_mm	5

### Dimensions

Dimensions b in mm	17
Dimensions a in mm	73
Dimensions c in mm	132.5



# Accessories

Order no.	Designation	Product type
4102220	Wireless receiver for measuring instruments with integrated wireless	i-Stick