

# Product information

## Measuring pistol Micromar 844 A

### Product features

- Threaded connection for changing the measuring head
- Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with a rotatable display

Item no.: **4487704**



### Package contains

excludes indicator, basic units 844 Ag, measuring head 44 Ak, instruction manual, case

### Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head)


- from:
- through holes
  - blind holes
  - centering shoulders

### Technical data

<b>Measuring range mm</b>	16 - 20 mm
<b>Measuring range</b>	.625 - .775"
<b>Error limit <math>\mu\text{m}</math></b>	3 $\mu\text{m}$
<b>Notes error limit</b>	<ul style="list-style-type: none"> <li>•Over the full length of the anvils</li> <li>•Indicator is not taken into consideration</li> </ul>

### Dimensions

<b>Dimensions b in mm</b>	6.5 mm
<b>Dimensions c in mm</b>	4 mm
<b>Dimensions d in mm</b>	64 mm



### Accessories

Order no.	Designation	Product type
4710040	Setting ring	355 E