# **Product information**

## Measuring pistol in set Micromar 844 AS

#### Product features

- · Threaded connection for changing the measuring head
- · Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with Item no.: 4487751 a rotatable display

#### Package contains

instruction manual, setting rings, key for replacing measuring heads (from 30 mm), case

#### Application

- Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:
- through holes
- blind holes

· centering shoulders



### **Technical data**

| Measuring range mm | 12 - 20 mm   |  |  |
|--------------------|--|--|--|
| Measuring range    | .4725775"  |  |  |
| Error limit µm     | 4 µm   |  |  |
| Notes error limit  | <ul><li>Over the full length of the anvils</li><li>Indicator is not taken into consideration</li></ul> |  |  |

#### Accessories

| Order no. | Designation                        | Product type |
|-----------|------------------------------------|--------------|
| 4102357   | Data<br>connection<br>cable USB    | 16 EXu       |
| 4102410   | Data<br>connection<br>cable RS232C | 16 EXr       |
| 4102915   | Data cable<br>Digimatic            | 16 EWd       |