# **Product information**

## Measuring pistol in set Micromar 844 AS

#### Product features

- · Threaded connection for changing the measuring head
- · Self-centering measuring head consists of 3 anvils (offset 3 x 120°)
- Measuring anvils from 12 mm are carbide tipped
- From 12 mm measuring anvils for measurements up to the bottom of the bore
- From 40 mm measuring head housing made of anodized aluminium
- Measuring value indication is always easy to read when using an electronic dial indicator with Item no.: 4487763 a rotatable display

#### Package contains

instruction manual, digital Indicator 1086 R, setting rings, key for replacing measuring heads (from 30 mm), case

#### Application

Fast measurements by lever retraction (covers the complete application range of the respective measuring head) from:

- through holes
- blind holes
- centering shoulders



### **Technical data**

Measuring range mm	50 - 100 mm	
Measuring range	2 - 4"	
Resolution mm/inch	0.0005 / .00002"	
Error limit µm	5 µm	
Notes error limit	<ul><li>Over the full length of the anvils</li><li>Indicator is not taken into consideration</li></ul>	
Battery type	CR 2450N (3V Lithium)	

#### **Accessories**

Order no.	Designation	Product type
4102357	Data connection cable USB	16 EXu
4102410	Data connection cable RS232C	16 EXr
4102915	Data cable Digimatic	16 EWd