

# Product information

## Calibration measuring instruments Precimar ULM 1500 L-E

### Package contains

Standard software 828 WIN  
"Free measuring", PC evaluation unit (without monitor), Magnetic holder for temperature probe, Support table, Pair of measuring brackets, immersion depth 14 mm, 2 parallel gage blocks 60/20, 2 quick clamps, 2 measuring heads with spherical zone, Setting gage 2, USB stick, Weights 0.25/0.5/1.0/2.0N, Hexagonal wrench, Screwdriver, Accessories package



### Application

Calibration of:

- Plain plug gages and gage rings
- Setting gage rings
- Snap gages
- Spherical gage blocks, internal micrometers
- Gage blocks
- Thread gages
- Taper thread gages
- Gear gages
- Taper gages
- Dial indicators
- Dial comparators
- 2-point bore gages
- Outside micrometers
- 2-point inside micrometers

Item no.: **5350264**

### Technical data

<b>Measuring range for outer measurement [mm]</b>	0 to 1620
<b>Measuring range for inner measurement [mm]</b>	0.5 to 1465
<b>Direct measuring range [mm]</b>	0 to 1115
<b>Measuring uncertainty <math>MPE_{E1}</math> (<math>L \leq (0,1+L/2000)</math> in mm) [<math>\mu m</math>]</b>	
<b>Repeatability [<math>\mu m</math>]</b>	$\leq 0,05$
<b>Measuring forces [N]</b>	0.2 ; 1.0 to 4.5 ; 11
<b>Device length [mm]</b>	2300
<b>Mass [kg]</b>	325
<b>Device dimensions</b>	2300 x 380 x 480