

Información de productos

Comparador de cuadrante mecánico MarCator 25M

Propiedades del producto

- Unit construction and removable movement save repair/cleaning time and maintenance
- Hardened gears and stainless steel racks provide lasting protection against indicator failure due to shock or wear
- Jeweled bearings resist friction, add to longer indicator life
- Skeletonized, hobbled gears for more sensitive response, superior indicator accuracy with minimal hysteresis error
- Soft tinted dials (green - inch / yellow - metric) minimize eye strain
- Special steel alloy
- Balanced dial hand affords no shift, precise reading
- Controlled rack and pinion mesh eliminates slope for precise response and reading
- Smooth adjusting bezels for easy setup
- Positive pressure pull back spring requires less maintenance
- Compliance with ANSI/AGD dimensional and accuracy specifications
- These indicators are normally furnished with continuous dial (with R.C.) or + on right balance dial (w/o R.C.), lug back and .18" by .250" long contact
- Optional Dials: balanced dial with + on left; continuous clockwise; continuous counterclockwise. (Order by part number and specify dial style desired)
- For other dial styles or special requirements - call Mahr



N.º de referencia: **2015786**

Datos técnicos

Rango de medición en pulgadas 0.07

Dimensiones

Dimensión B en pulgadas (texto)	2"
Dimensión A en pulgadas (texto)	2.25"
Dimensión D en pulgadas (texto)	0,719"
Dimensión C en pulgadas (texto)	2.063"
Dimensión E en pulgadas (texto)	0,344"

