

**Mahr**

Mahr | A passion for detail

**Edition**  
2024

# Autumn Sale

## Mobile roughness measurement with the MarSurf M 310

- Intuitive and easy to operate like a smartphone
- Immediate measuring success thanks to program start via barcode scanner
- Uncomplicated digital connection to QM systems



**Special offer prices**

October 1 - December 31, 2024

# Comprehensive product range with Integrated Wireless

Mahr offers a comprehensive range of measuring instruments with integrated wireless data transmission for use in all areas of industrial manufacturing and quality control. The Integrated Wireless range from Mahr delivers accurate measuring results with full mobility. Modern, simple measuring solutions – without the limitations of wired technology.

4

Product groups

85

Products



MarCal 16 EWRI

Digital calipers



MarCator 1086 Ri

Digital indicators



Micromar 40 EWRI

Digital outside micrometers



MarCator 1086 Ri  
with stand

Digital indicators




MarCator 1086 Ri  
with 3-point pistol

Digital indicator



Millimes  
2001 Wi

Digital  
comparator




MarCator 1087 Ri  
with SM 60

Digital indicator


# MarCal 16 EWRI / 30 EWRI

## Digital calipers with wireless interface



4103400


1493.00  
MarCal 16 EWRI



4112571

5063.00  
MarCal 18 EWRI

When things start to get bigger




4126751

2243.00  
MarCal 30 EWRI

Compact and handy

always within reach



4126671

2985.00  
MarCal 30 EWRI

Order no.	Product	Measuring range	Resolution	Depth rod	Details	List price	Offer price
		mm	mm			DKK	DKK
4103400	16 EWRI	0 – 150	0.01	round	With measuring blades	<del>1853.00</del>	1493.00
4103402	16 EWRI	0 – 150	0.01	square	With measuring blades	<del>1853.00</del>	1493.00
9105795	16 EWRI	0 – 150	0.01	round	Starter pack incl. i-Stick	<del>2742.00</del>	2018.00
9105796	16 EWRI	0 – 150	0.01	square	Starter pack incl. i-Stick	<del>2742.00</del>	2018.00
4112571	18 EWRI	0 – 300	0.01		With measuring blades	<del>5826.00</del>	5063.00
4112572	18 EWRI	0 – 500	0.01		With measuring blades	<del>7568.00</del>	6570.00
4126671	30 EWRI	0 – 150	0.01		With measuring pin Ø 1,5 mm	<del>3442.00</del>	2985.00
4126672	30 EWRI	0 – 200	0.01		With measuring pin Ø 1,5 mm	<del>3898.00</del>	3383.00
4126673	30 EWRI	0 – 300	0.01		With measuring pin Ø 1,5 mm	<del>4479.00</del>	3885.00
4126751	30 EWRI	0 – 25	0.01		With measuring pin Ø 2 mm	<del>2592.00</del>	2243.00

Accessories for measuring instruments with Integrated Wireless							
4102220	i-Stick	Wireless receiver for measuring instruments with integrated wireless				<del>889.00</del>	713.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>  
All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

Autumn Sale

# Micromar 40 EWri

Micrometers according to your wishes



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4157100	40 EWri	0 – 25	0.001	Standard version	<del>2562.00</del>	2063.00
4157101	40 EWri	25 – 50	0.001	Standard version	<del>3024.00</del>	2438.00
4157115	40 EWri	0 – 100	0.001	Standard version. set with 4 micrometers	<del>13553.00</del>	10920.00
4157120	40 EWri-L	0 – 25	0.001	QUICK DRIVE, 5 mm per rotation	<del>3195.00</del>	2573.00
4157121	40 EWri-L	25 – 50	0.001	QUICK DRIVE, 5 mm per rotation	<del>3642.00</del>	2933.00
4157150	40 EWri-V		0.001	Universal micrometer (QUICK DRIVE) incl. measuring anvils	<del>9309.00</del>	7463.00

Accessories for measuring instruments with Integrated Wireless					List price	Offer price
4102220	i-Stick	Wireless receiver for measuring instruments with integrated wireless			<del>889.00</del>	713.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 30, 2024

# MarCator 1086 Ri / 1087 Ri

Practically suited to your measuring tasks





**3578.00**  
MarCator 1087 Ri

4337663





**3060.00**  
MarCator 1086 Ri

4337624

Millimess | Inductive dial comparators

# Millimess 2000 Wi / 2001 Wi

see also page 14





**4665.00**  
Millimess 2000 Wi

4346701





**5243.00**  
Millimess 2001 Wi

4346801

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4337624	1086 Ri	12.5	0.0005	Practical functions for static measurement tasks	<del>3798.00</del>	3060.00
4337625	1086 Ri	25	0.0005	Practical functions for static measurement tasks	<del>4290.00</del>	3458.00
4337663	1087 Ri	12.5	0.0005	Practical functions for static and dynamic measurement tasks	<del>4414.00</del>	3578.00
4337665	1087 Ri	25	0.0005	Practical functions for static and dynamic measurement tasks	<del>5027.00</del>	4050.00
4346701	2000 Wi	± 1	0.0001	Highest sensitivity and accuracy, for static measuring tasks	<del>5786.00</del>	4665.00
4346801	2001 Wi	± 1	0.0001	Highest sensitivity and accuracy, for static and dynamic measuring tasks	<del>7354.00</del>	5243.00

Accessories for measuring instruments with Integrated Wireless					List price	Offer price
4102220	i-Stick	Wireless receiver for measuring instruments with integrated wireless			<del>889.00</del>	713.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>  
All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024




# MarCal 16 ER / 16 EWR

Digital calipers without data output

Best Price – Best Quality!

The standard  
in the workshop



4103010

735.00  
MarCal 16 ER



1095.00  
MarCal 16 EWR

4103300

The insensitive caliper  
for production and workshop

Order no.	Product	Measuring range	Resolution	Depth rod	Details	List price	Offer price
		mm	mm			DKK	DKK
4103010	16 ER	0 – 150	0.01	round	Lapped guideway	<del>909.00</del>	735.00
4103012	16 ER	0 – 150	0.01	square	Lapped guideway	<del>909.00</del>	735.00
4103205	16 ER	0 – 200	0.01	square	Lapped guideway	<del>1483.00</del>	1290.00
4103300	16 EWR	0 – 150	0.01	round	Protection class IP 67	<del>1352.00</del>	1095.00
4103302	16 EWR	0 – 150	0.01	square	Protection class IP 67	<del>1352.00</del>	1095.00
4103304	16 EWR	0 – 200	0.01	square	Protection class IP 67	<del>1949.00</del>	1695.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 30, 2024

# MarCal 30 EWR


## Digital depth gages



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4126651	30 EWR	0 – 150	0.01	Protection class IP67	<del>3014.00</del>	2618.00
4126652	30 EWR	0 – 200	0.01	Protection class IP67	<del>3504.00</del>	3045.00
4126653	30 EWR	0 – 300	0.01	Protection class IP67	<del>3981.00</del>	3458.00

# MarCal 16 FN

## Pocket calipers



Order no.	Product	Measuring range	Vernier value	Depth rod	List price	Offer price
		mm	mm/inch		DKK	DKK
4100400	16 FN	0 – 150	0.05/1/128"	square	<del>251.00</del>	218.00
4100401	16 FN	0 – 200	0.05/1/128"	square	<del>581.00</del>	593.00

# Micromar 40 ER / 40 EWR

The insensitive ones for production and workshop

Autumn Sale



4157010



4157020



4157050

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4157010	40 ER	0 – 25	0.001	Protection class IP40	<del>1456.00</del>	1170.00
4157011	40 EWR	0 – 25	0.001	Protection class IP65	<del>1974.00</del>	1463.00
4157012	40 EWR	25 – 50	0.001	Protection class IP65	<del>2510.00</del>	2025.00
4157020	40 EWR-L	0 – 25	0.001	IP65, data output, QUICK DRIVE, 5 mm per rotation	<del>3106.00</del>	2505.00
4157021	40 EWR-L	25 – 50	0.001	IP65, data output, QUICK DRIVE, 5 mm per rotation	<del>3545.00</del>	2858.00
4157050	40 EWR-V	0 – 25	0.001	IP65, data output, universal micrometer QUICK DRIVE in a set	<del>9048.00</del>	7290.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 30, 2024



# Micromar 40 A / 40 SA / 40 AS

Basics for production and workshop

Autumn Sale

Outside micrometers with  
hard lacquered steel frame



4134000

398.00  
Micromar 40 A



2318.00  
Micromar 40 SA/SET

4134050

3-point inside micrometers  
suited for blind bores (from  
12mm)



13440.00  
Micromar 44 AS/SET



4190352

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4134000	40 A	0 – 25	0.01	Glare-free matt chrome-plated display parts	<del>492.00</del>	398.00
4134001	40 A	25 – 50	0.01	Glare-free matt chrome-plated display parts	<del>771.00</del>	623.00
4134050	40 SA/SET	0 – 100	0.01	Set of 4 micrometers	<del>2875.00</del>	2318.00
4190350	44 AS/SET	6 – 12	0.001	incl. setting rings 8 mm, 10 mm	<del>9644.00</del>	7770.00
4190351	44 AS/SET	12 – 20	0.001	incl. setting ring 16 mm	<del>7372.00</del>	5940.00
4190352	44 AS/SET	20 – 50	0.005	incl. setting rings 25 mm, 40 mm	<del>16680.00</del>	13440.00
4190353	44 AS/SET	50 – 100	0.005	incl. setting rings 60 mm, 85 mm	<del>19845.00</del>	15990.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>  
All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

# Micromar 44 EWR / 844 AS

Digital 3-point internal me  
precision is guaranteed



17160.00  
Micromar 44 EWR/SET



4191162

Measure holes

in one movement



4487762

17760.00  
Micromar 844 AS/SET



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4191160	44 EWR/SET	6 – 12	0.001	incl. setting rings 8 mm, 10 mm	<del>15824.00</del>	12743.00
4191161	44 EWR/SET	12 – 20	0.001	incl. setting ring 16 mm	<del>13776.00</del>	11100.00
4191162	44 EWR/SET	20 – 50	0.001	incl. setting rings 25 mm, 40 mm	<del>21297.00</del>	17160.00
4191163	44 EWR/SET	50 – 100	0.001	incl. setting rings 60 mm, 85 mm	<del>25542.00</del>	20580.00
4487760	844 AS/SET	6 - 12	0.0005	incl. digital indicator 1086 R and setting rings 8 mm, 10 mm	<del>16792.00</del>	13530.00
4487761	844 AS/SET	12 - 20	0.0005	incl. digital indicator 1086 R and setting rings 16 mm	<del>15005.00</del>	12090.00
4487762	844 AS/SET	20 - 50	0.0005	incl. digital indicator 1086 R and setting rings 25 mm, 40 mm	<del>22042.00</del>	17760.00
4487763	844 AS/SET	50 - 100	0.0005	incl. digital indicator 1086 R and setting rings 60 mm, 85 mm	<del>26793.00</del>	21540.00


Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 30, 2024

# MarTest 800 S / 800 SG / 800 SM

Highly sensitive measuring


**915.00**  
MarTest 800 SGM



4308200

**Ideal**  
when absolute precision is vital


**638.00**  
MarTest 800 S



4305200

**Ideal**  
for confined spaces

**1028.00**  
MarTest 800 SL



4306200

**Ideal**  
when greater depth is needed

MarCator | Dial indicator

# MarCator 810 A



4311050

**300.00**  
MarCator 810 A

Order no.	Product	Measuring range	Graduation value	Details	List price	Offer price
		mm	mm		DKK	DKK
4305200	800 S	± 0.4	0.01	Dial ø 28 mm, measuring insert length 14.5 mm	<del>790.00</del>	638.00
4307200	800 SG	± 0.4	0.01	Dial ø 38 mm, measuring insert length 14.5 mm	<del>797.00</del>	645.00
4308150	800 SM	± 0.1	0.002	Dial ø 28 mm, measuring insert length 14.5 mm	<del>1028.00</del>	833.00
4308200	800 SGM	± 0.1	0.002	Dial ø 38 mm, measuring insert length 14.5 mm	<del>1136.00</del>	915.00
4306200	800 SL	± 0.25	0.01	Dial ø 28 mm, measuring insert length 41.24 mm	<del>1274.00</del>	1028.00
4311050	810 A	10	0.01	High-contrast dial face	<del>395.00</del>	300.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>  
All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

# MarCator 1075 R / 1086 R / 1087 R

Practically suited to your measuring tasks

Autumn Sale



1095.00

MarCator 1075 R



4336010



3255.00

MarCator 1087 R

4337660



2588.00

MarCator 1086 R



4337620

# MarCator 1086 R-HR / 1087 R-HR

Highest precision with a large measuring range



Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4336010	1075 R	12.5	0.01	Basic functions for static measuring tasks	<del>1359.00</del>	1095.00
4336020	1075 R	12.5	0.005	Basic functions for static measuring tasks	<del>1869.00</del>	1493.00
4336030	1075 R	12.5	0.001	Basic functions for static measuring tasks	<del>2793.00</del>	2235.00
4337130	1086 R	12.5	0.01	Practical functions for static measurement tasks	<del>2607.00</del>	2100.00
4337620	1086 R	12.5	0.0005	Practical functions for static measurement tasks	<del>3187.00</del>	2588.00
4337621	1086 R	25	0.0005	Practical functions for static measurement tasks	<del>3932.00</del>	3165.00
4337660	1087 R	12.5	0.0005	Practical functions for static and dynamic measurement tasks	<del>4044.00</del>	3255.00
4337661	1087 R	25	0.0005	Practical functions for static and dynamic measurement tasks	<del>4647.00</del>	3743.00
4337697	1086 R-HR	12.5	0.0001	High-resolution, practical functions for static measurement tasks	<del>4915.00</del>	3960.00
4337695	1087 R-HR	12.5	0.0001	High-resolution, practical functions for static and dynamic measurement tasks	<del>5831.00</del>	4695.00

# Highest level of precision

Autumn Sale



## Integrated Wireless

- Integrated Wireless interface
- Sending and receiving measuring data and various parameters



Can be configured and controlled remotely using MarCom Professional Software



## Bidirectional data interface via USB

- Sending and receiving measuring data and various parameters
- Permanent power supply via data cable
- Possible to retrieve the device ID

#ID



## Data interface via Digimatic

- To send measuring data



## Lock individual keys and functions

Remote-controlled settings can be configured easily using MarCom Professional Software



## First digital comparator indicator with touch operation

Extensive advantages:

- Keys react even with the slightest touch
- This prevents a measuring device from being adjusted or deformed – **maximum measuring certainty**

## Hardened glass front

- Scratch and impact-resistant surface
- Excellent protection against scratches and penetrating liquids
- Wear-free keys react to the slightest touch

## High-precision ball-bearing guide

Maximum sensitivity of the measuring system, long service life, and high loading capacity



## Protection rating IP 64

Excellent protection against dust and splash water from all directions ensures optimum workshop compatibility at all times




## Convenient tolerance functions

- Clear tolerance symbols
- Colorful LED signals (red, green, yellow) to classify the measuring values
- No go/Go/warning limit
- No go/Go/rework

## High precision inductive measuring system

Lowest measuring deviations thanks to linearization



## ABS system

## Absolute measuring system

The reference to the electric zero point is not lost when the device is switched off



# Millimes 1002 / 1003 / 1010 / 2000 W / 2001 W

Everything reliably under control

Autumn Sale

1095.00

Millimes 1010



4332000

1470.00

Millimes 1003



4334000

4395.00

Millimes 2000 W



4346700

4965.00

Millimes 2001 W



4346800

Order no.	Product	Measuring range		Display resolution		Details	List price	Offer price
		mm	µm	mm	µm		DKK	DKK
4335000	1002		± 25		0,5	Precision ball bearing of measuring spindle	<del>3277.00</del>	2640.00
4334000	1003		± 50		1	Precision ball bearing of measuring spindle	<del>1829.00</del>	1470.00
4334001	1003 XL		± 130		2	Precision ball bearing of measuring spindle	<del>1829.00</del>	1470.00
4332000	1010		± 250		10	Precision ball bearing of measuring spindle	<del>1363.00</del>	1095.00
4346700	2000 W	± 1		switchable 0.0001 ... 0.01 mm/ .000005" ... .0005"		Inductive measuring system, practical functions for static measuring tasks	<del>5451.00</del>	4395.00
4346800	2001 W	± 1		switchable 0.0001 ... 0.01 mm/ .000005" ... .0005"		Inductive measuring system, practical functions for static and dynamic measuring tasks	<del>6166.00</del>	4965.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>  
All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

# Millimar C 1202

## Flexible evaluation and display anywhere

**The Millimar C 1202 compact instrument is versatile and suitable for use with a variety of sensors.**

The Millimar C 1202 represents the next generation of multichannel compact instruments for length metrology. Due to its sophisticated features such as the tilting easy-to-read display, clear menu navigation and flexible representation of measuring values, it offers maximum ergonomics and user-friendliness. Combine with an easy to change module from the N 1700 series to create just the right measuring instrument for your measuring task. Thanks to its wide range of functions, the Millimar C 1202 is extremely versatile. It can be used to tackle a multitude of measuring tasks, e.g. static and dynamic measurements as well as cone calculations. Moreover, depending on the module, measuring probes by other manufacturers may also be compatible, which will reduce your costs.

### Tilting display

Measuring values can be read clearly and effortlessly from all viewing angles. The display also features a backlight.

### Sturdy plastic housing

As the Millimar C 1202 is impervious to external influences, it is ideal for use in production.

### Interchangeable modules

The Millimar C 1202 can be easily converted to handle different measuring tasks.

### Configuring C 1202

#### Possible combinations with N 1700 modules

N 1702 M/M-HR/T/U



N 1702 VPP



N 1701 PF/PM



End plate included in delivery of Millimar C 1202



1x N 170x module or 2x N 1701 PF/PM



Extension rail, 2x N 1701 PF/PM



C 1202

# 9

**Different N 1700 modules**  
can be combined with Millimar C 1202

## Interpret measuring results with ease

The high contrast color display provides a clear presentation of the measuring results.

## Large keys

The Millimar C 1202 can also be reliably operated with gloves. Even dirt does not impede its function.



## Advantages

- Three features can be displayed at the same time – for even more static and dynamic measuring tasks
- Two independent inputs via N 1700 module for the optional connection of measuring probes and pneumatic transducers
- Interchangeable modules for flexibility and compatibility
- Digimatic and USB ports for easy connection to data collection systems and evaluation software
- Programmable measuring sequences for greater productivity and reliability

## Flexible setup options

Users can position the instrument on the table or fix it to the wall.



# Millimar C 1200 / 1318 / P 2004

Smart and universal application

Autumn Sale



5312012

7110.00  
Millimar C 1200 M

Compatibility:  
M = Mahr

5145.00  
Millimar 1318



5313180

2010.00  
Millimar P 2004 M



5323010

Order no.	Product	Numerical display	Resolution	Details	List price	Offer price
5312012	Millimar C 1200 M	µm ± 5000	µm 0.1	High-resolution, high-contrast TFT color display	DKK <del>9459.00</del>	DKK 7110.00

Order no.	Product	Measuring range	Measuring force	Details	List price	Offer price
5323010	P 2004 M	mm ± 2	N 0.75	Inductive probe	DKK <del>2674.00</del>	DKK 2010.00
5313180	1318	- 0.3 ... 1	0.25 +/-0.05	Dial test indicator inductive probe	DKK <del>6849.00</del>	DKK 5145.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

# Millimar C 1202 / N 1702 / P 2004 / P 1512 / P 1530

## Flexible evaluation and display anywhere



5312025

**6090.00**  
Millimar C 1202



5331120

**2685.00**  
Millimar N 1702 M



5331125

**5708.00**  
Millimar N 1702 M-HR



5331161

**2513.00**  
Millimar N 1702 VPP



5315081

Order no.	Product	Numerical display	Resolution	Details	List price	Offer price
5312025	Millimar C 1202	$\mu\text{m}$ $\pm 999\,999.9$	$\mu\text{m}$ 0.01, 0.1, 1	High-resolution, high-contrast TFT color display	<del>8102.00</del> DKK	<b>6090.00</b> DKK

Order no.	Product	Measuring range	Measuring force	Details	List price	Offer price
5331120	Millimar N 1702 M	mm $\pm 2$	N	Module for 2 inductive probes, Resolution 0.1 $\mu\text{m}$	<del>3568.00</del> DKK	<b>2685.00</b> DKK
5331125	Millimar N 1702 M-HR	$\pm 0.2$		Module for 2 inductive probes, Resolution 0.1 $\mu\text{m}$	<del>7591.00</del>	<b>5708.00</b>
5323010	P 2004 M	$\pm 2$	0.75	Inductive probe	<del>2674.00</del>	<b>2010.00</b>
5313180	1318	- 0.3 ... 1	0.25 +/- 0.05	Inductive lever probe	<del>6849.00</del>	<b>5145.00</b>
5331161	Millimar N 1702 VPP			Module for incremental sensors	<del>3345.00</del>	<b>2513.00</b>
5315081	P 1512 V	12	0.6 – 1.2	Incremental probe	<del>6562.00</del>	<b>5235.00</b>
5315311	P 1530 V	30	0.4 – 1	Incremental probe	<del>9100.00</del>	<b>7268.00</b>



# Digimar 817 CLT

## Reaching great heights with maximum precision and flexibility



### Best connection for secure data

Data can be transferred wirelessly or via USB cable via the MarConnect interface. Quickly print out a series of measurements with the available Star Micronics SM-L200 Bluetooth® printer. Simply choose between complete measuring records in PDF format or save your measuring records as a TXT file.



### Interfaces for dial indicators

An interface integrated in the slide enables the error-free measurement of the perpendicularity and straightness using the new Millimes 2000/2001W dial comparators.



# 47655.00

Digimar 817 CLT



### Simple touch measurement

Intuitive operation via large, clearly defined keys to ensure the safe completion on measurements, setting and calculation of functions, and the creation of measuring programs via Drag & Drop.



### Pivoting display

10-inch touch panel with turn/tilt joint so that it can be set individually for the work position, height of the operator, and lighting conditions.



### Easy handling

The thumbwheel can be used to move the measuring slide quickly and easily start the measurement. The quick measurement function keys also automatically detect surfaces and bores.



4429600

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4429600	817 CLT	0 – 350	0.01, 0.005, 0.001, 0.0005, 0.0001	Error limit (1.8 + L/600) L in mm	<del>59667.00</del>	47655.00
4429601	817 CLT	0 – 600	0.01, 0.005, 0.001, 0.0005, 0.0001	Error limit (1.8 + L/600) L in mm	<del>65135.00</del>	52020.00
4429602	817 CLT	0 – 1000	0.01, 0.005, 0.001, 0.0005, 0.0001	Error limit (1.8 + L/600) L in mm	<del>99099.00</del>	79140.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 30, 2024



# Digimar 814 SR

Ideal for the workshop, robust and universally applicable.

Autumn Sale


## Digimar 814 SR Height Measuring and Scribing Instrument

Exact positioning by handwheel

4643.00  
Digimar 814 SR



4426100



Clamping lever

for quickly securing the slide unit

Handwheel

for easy positioning and measuring

Order no.	Product	Measuring range	Resolution	Details	List price	Offer price
		mm	mm		DKK	DKK
4426100	814 SR	0 – 350	0.01	Digit height 12 mm, handwheel for positioning and measuring	<del>6179.00</del>	4643.00
4426101	814 SR	0 – 600	0.01	Digit height 12 mm, handwheel for positioning and measuring	<del>10697.00</del>	8040.00

# Precimar SM 60 / SM 60-V

Simple and robust, ideal for production and QA

Autumn Sale

**Precise measuring results**

Thanks to the spring-loaded measuring spindle with high-precision bearing

**Mount**

for measuring equipment (digital dial indicator, probes, etc.)

**Clamping lever**

for securing the contact

**Clamping screw**

for securing the support table


**Lifting lever**

for easy positioning of the measuring probe

5357360

**12300.00**

Precimar SM 60



**13020.00**

Precimar SM 60-V

**SM 60-V**

for universal use due to interchangeable measuring inserts

5357380

**Application example:**

Measurement of the diametral two-ball dimension of a gear



Order no.	Product	Measuring range	Application range	Mount ø	Details	List price	Offer price
		mm	mm	mm		DKK	DKK
5357360	SM 60	25	0 – 60	8	Table size ø 60 mm	<del>18450.00</del>	12300.00
5357380	SM 60-V	25	0 – 60	8	Table size ø 60 mm, incl. pair of carbide anvils Ø 3.5 mm	<del>19530.00</del>	13020.00

# Precimar ICM 100 IP

## Fast & reliable data collection

The powerful USB 3.0 camera and sturdy LED lighting guarantee that all display values are clearly legible. Even when the scale or numerical display of your testpiece are not exactly centered in the image, the system will read the displayed values perfectly.

188,250.00  
Precimar ICM 100 IP

## One-handed operation

Using just one hand and no tools, you can move the camera and light source to the optimal height and position for your measurement: Fold down the lever, adjust the height continuously – done. Handling is easy and, thanks to spring-supported weight reduction, particularly comfortable and ergonomic.

## Universal & reliable

The Precimar ICM 100 IP based on the tried-and-tested Precimar ICM 100 dial indicator test station – also known as Optimar 100. This versatile, market-tested solution can be used for checking analog and digital dial indicators as well as dial comparators by a wide range of manufacturers. It provides traceable measuring results conforming to standards in a measuring range of up to 100 mm.

5351010

## Manual mode

Do you want to check your testpieces manually in individual cases? You can still do so with easy handwheel operation. In manual mode, the camera serves as a magnifying glass. Thanks to the enlarged live image, you can read the display values more easily, thus making manual work faster and more reliable.

Order no.	Product	Measuring range	Measuring uncertainty $MPE_{E1}$	Details	Offer price
		mm / inch	$\mu m$		DKK
5351010	Precimar ICM 100 IP	100 / 4	$0.2 + L / 250$	Incremental measuring system, USB 3.0 CMOS camera. PC, mouse, keyboard, monitor, software and commissioning are <b>not included</b> in the price	188,250.00

Accessories				
5358001	ICM100 software	Basic software		12203.00

# MarSurf PS 10

## Mobile measuring made easy

The MarSurf PS 10 is the ideal entry level instrument for surface metrology: Its extraordinarily simple and intuitive operation, along with numerous safety functions including the automatic cutoff, make the device as easy to control as a cellphone. Due to its minimal size, it is also perfect for location-independent measurements – vertical, horizontal and even overhead if necessary. And thanks to the removable drive unit, the MarSurf PS 10 can be used flexibly in production.

The measuring instrument boasts three order options for increased flexibility: with stylus tip 2 µm, 5 µm and also a variant with a transverse drive unit (MarSurf PS 10 C2).

- Intuitive operation: As easy as using a smartphone with a rotatable display
- Creates complete PDF measuring records right in the measuring instrument and data backup as TXT, X3P, CSV and PDF files
- Customized comments for the PDF measuring record entered directly into the MarSurf PS 10
- Error-free operation thanks to an integrated, removable roughness standard
- Automatic cutoff selection, ensuring that even non-specialists get the correct measuring results

9

other optional  
probes

### Always at hand

The calibration standard stays in the instrument and can be checked at any time.

500 g  
lightweight




### Extremely easy to operate with detailed profile display

The large 4.3" high-resolution and backlit TFT touch display allows intuitive operation and precise representation of the measuring profile.

### Perfect evaluation and documentation

Measuring records are automatically created in the instrument without the need for additional software.



### Flexible use

The removable drive unit, in conjunction with the optional handheld support, lends this instrument added versatility where space is limited, e.g. in holes or when measuring small parts.

up to

# 500,000

**measurements**  
can be stored in the instrument

# 31

**parameters**  
same range of functions as a  
laboratory instrument

# 4.3"

**TFT touch display**  
similar to a smartphone

at least

# 1,200

**measurements**  
without power supply

## 14963.00

**MarSurf PS 10**



6910230

Order no.	Product	Measuring range	Probe	Details	List price	Offer price
6910230	PS 10	µm 350	Skidded probe system	Storage capacity for min. 3900 profiles, min. 500,000 results, min. 1500 PDF protocols, expandable with microSD card up to 32 GB	DKK <del>19986.00</del>	DKK <b>14963.00</b>

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>  
All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

## MarSurf M 310

### Brings added value for mobile roughness measurement

Are you used to using your smartphone to access your data anytime, wherever you are? That is exactly what Mahr's MarSurf M 310 provides you with: A versatile device for the mobile recording and evaluation of measuring data. Simple operation and a robust design

make this Mahr product perfectly suited for use in production, where dirt and dust can clog the instrument and it is often users with little prior knowledge performing the quality control.

## For all those who need more

The **MarSurf M 310** has the same functions as the PS 10 but has even more crucial added benefits for you:

- 1 Print directly, document easily**  
Measuring results in paper form? Sometimes still the fastest way! The mobile printer allows you to save data on thermal paper, which can then be added directly to the workpiece.
- 2 Preprogrammed measuring functions for immediate measuring success**  
A variety of measuring parameters can be defined, saved and then called up on the workpiece in the device settings. Additionally, it works using a barcode scanner, which simply connects to the MarSurf M 310. This allows even workers without expert knowledge or training to determine reliable roughness parameters.
- 3 Robot ready: Integrate instrument directly in the production line**  
The MarSurf M 310 and its interfaces can be directly integrated into your production lines, such as for measuring tasks on the robot arm. They control the measuring instrument remotely – conveniently from your computer, for example.

### Status at a glance

Instrument status at a glance thanks to two easily visible status LEDs. Depending on the signal color, a measurement is underway, data is being transferred or an error has been detected. Standby mode shows the charging status.

### Robust in every respect

Equipped for virtually any environment: The robust skidded probe system means that the measuring instrument is less sensitive to vibrations. The PHT probe is easy to clean due to its open skid.



### Modern optics, perfect display

A high resolution, backlit 4.3" TFT display ensures precise display of your measuring results. It is operated directly via the touchscreen – just as you are used to with your smartphone.

### IATF compliant

The MarConnect duplex interface enables the transmission of a measuring equipment ID with each measurement. This makes measuring results traceable at any time.



### Software with a success guarantee

With this measuring instrument, you can reliably determine roughness parameters even without expert knowledge or training – due to intuitive software, clear menu structures and preprogrammed measuring functions.



**21675.00**

MarSurf M 310 SET



6910260

Order no.	Product	Measuring range	Probe	Details	List price	Offer price
		µm			DKK	DKK
6910260	MarSurf M 310 SET	350	Skidded probe system 2 µm probe tip	Storage capacity for min. 3900 profiles, 1500 PDF protocols and 500,000 results, expandable with microSD card up to 32 GB	<del>26229.00</del>	21675.00
6910267	MarSurf M 310 SET with printer	350	Skidded probe system 2 µm probe tip	Additionally with Star Micronics SM-L200 USB/Bluetooth® printer and docking station for direct printout of profiles, ADC and MRC diagram and measurement results	<del>30086.00</del>	24863.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

## MarSurf M 410

Simple, innovative, flexible –  
modern surface metrology  
to be used by hand

Mobile recording and evaluation of measuring data has never been this easy. The MarSurf M 410 is convenient and flexible to use – just a like a modern smartphone. It has a practical touch display, an integrated PDF memory, innovative accessories, and wireless data transfer – all of which effectively simplify your workload.

Benefit from functions that only Mahr can offer you. In addition to the practical and efficient design and the flexibility this offers, the MarSurf M 410 also has an automatic filter setting by detecting the surface structure. This automatic contacting also guarantees the unmatched reliability of your measurements. The magnetic 3-point holder for the probe arm and the freely combinable accessories offer additional process security.




### Advantages

- Increased efficiency thanks to large integrated memory: More than 500,000 measuring programs and 1,500 PDF reports, can be expanded by 32 GB (microSD)
- Skidless probes ensure that the roughness and waviness can be measured without an additional measuring station being required – determination of parameters R, W and P.
- Safe measuring results thanks to automated cutoff option
- Automatic zeroing ensures process and material safety
- IATF ready – simply activate/deactivate in the menu by automatically transferring the item and serial number of the measuring instrument
- Free MarCom software to transfer data

### Possible to separate the display and probe system

Optionally, you can use the measuring instrument as a mini mobile measuring station, for example by simply attaching the display to the wall using the supplied pivoted docking station.



### Magnetic probe holder

Probe arms can be changed quickly without tools and with additional protection: The magnetic 3-point holder ensures that the probe will not be broken in the event of a collision; it will simply be released by the magnetic holder.

## Simple alignment of the probe system

The inclination is easy to correct via the menu-driven, graphic instructions.

## Intuitive operation via touch display

Easy to operate just like a smartphone so that no training or introduction to the operating functions is required – you can just get started.

## Creation of PDFs directly on the device

Practical: The device creates a complete PDF file without the need for additional software or transfer to a computer. Information can be added to the PDF files directly on the device.

## Wireless data transmission

Connect your measuring device wirelessly to a PC, for example, and transfer your data to Microsoft Excel or other evaluation software.

## Importing information using a scanner

Simply start your measuring program by scanning a QR or barcode. You do not need to enter any profile information as your saved measuring programs are linked with a corresponding code.

**56438.00**

**MarSurf M 410 SET**

6910290

Order no.	Product	Measuring range	Probe	Details	List price	Offer price
		$\mu\text{m}$			DKK	DKK
6910290	MarSurf M 410 Set	500 $\mu\text{m}$ ( $\pm 250 \mu\text{m}$ )	with probe arm length 45 mm bis 1500 $\mu\text{m}$ ( $\pm 750 \mu\text{m}$ ) with probe arm length 135 mm	Storage capacity for min. 3900 profiles, 1500 PDF protocols and 500,000 results, expandable with microSD card up to 32 GB (increases the storage capacity by a factor of 320)	<del>68272.00</del>	<b>56438.00</b>
6910291	MarSurf M 410 Set (incl. printer)	500 $\mu\text{m}$ ( $\pm 250 \mu\text{m}$ )	with probe arm length 45 mm bis 1500 $\mu\text{m}$ ( $\pm 750 \mu\text{m}$ ) with probe arm length 135 mm	Additionally with Star Micronics SM-L200 USB/Bluetooth® printer and docking station for direct printout of profiles, ADC and MRC diagram and measurement results	<del>72129.00</del>	<b>59625.00</b>

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>


All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024

# MarSurf CD 140 AG 11

## Versatile with intelligent probe system


**Mahr has launched a new contour measuring machine on the market – the MarSurf CD 140 AG 11. Its probe system has a measuring range of up to 70 mm and the stylus tips can be replaced quickly and without any tools – without having to recalibrate the system.**

The new contour measuring machine MarSurf CD 140 AG 11 enables the user to complete fast and precise measurements. Its flexible workpiece holder makes it particularly easy to handle, while users are also convinced by its extreme versatility – it can also be used to measure roughness. The intelligent probe system and magnetic stylus tip holder ensure the process to replace stylus tips without any tools is the most straightforward process to date. Operators can also choose from a comprehensive range of clamps and workpiece holders. The new MarSurf CD 140 AG 11 can be used in a static position or directly at the location of the workpiece.



### Advantages

- Comprehensive contour measurement functions – fast and simple
- Quick adjustment of the Z-axis with handles that are simple to operate
- Replacement of the stylus tip without any tools
- Travel speed in the X-axis of up to 200 mm/s
- Simple program creation or single measurement using MarWin
- Automatic evaluation, best adjustment of contours, CAD contour comparison, and a lot more
- Flexible support plate with 50 mm bore grid for KMG workpiece holder, amongst other
- Optionally expandable with option of roughness measurements ( $R_z > 2 \mu\text{m}$ )
- Measurement with double stylus



Plug-in guide stops and a wide range of standardized clamping devices as well as workpiece holders enable flexible positioning of your testpiece.



### Manual quick adjustment

The fine adjustment is located in the Z-axis and moves the X-axis up and down.

### X-axis with maximum measuring range

The high-speed X-axis is designed for a large measuring range of 140 mm.

### Unique probe system

The probe system with a probe arm length of 350 mm enables a quick change of stylus tips without any tools and without having to recalibrate. The automatic tracing force selection guarantees the correct tracing force is selected when replacing several stylus tips.

### Support plate also for large components

The 390 mm x 450 mm large plate with 50 mm matrix of holes is also suitable for large-volume workpieces. This provides a variety of flexible clamping options.

### Ergonomic carrying handles

The handles on the side make it easy to transport the device.

### Generous traverse path

The Y-axis can be adjusted manually with a traverse path of 60 mm.

**134,925.00**

MarSurf CD 140 AG 11

6269200

Order no.	Product	Measuring range	Probe	Details	Offer price
		µm			DKK
6269200	MarSurf CD 140 AG 11	70 mm	with probe arm length 350 mm	Measuring force 4 mN to 30 mN, adjustable via software, measuring speed 0.1 mm/s to 10 mm/s, positioning speed X: 0.1 mm/s to 200 mm/s	134,925.00
6269202	MarSurf CD 140 AG 11 (incl. option Roughness)	70 mm	with probe arm length 350 mm	Measuring force 4 mN to 30 mN, adjustable via software, measuring speed 0.1 mm/s to 10 mm/s, positioning speed X: 0.1 mm/s to 200 mm/s	149,925.00

Detailed information on the products can be found at <https://metrology.mahr.com/en-int/>

All illustrations and figures etc. are without guarantee. All prices quoted are non-binding recommended prices. The net prices in € plus VAT are valid from October 1, 2024 to December 31, 2024


**Mahr**

**Mahr GmbH**  
Carl-Mahr-Straße 1  
37073 Göttingen  
Germany

Reutlinger Straße 48  
73728 Esslingen  
Germany

Phone: +49 551 7073 800  
info@mahr.com  
www.mahr.com

**Available from:**



© Mahr GmbH

We reserve the right to make changes to our products,  
especially due to technical improvements and further developments.  
All illustrations, numerical values, etc. are therefore subject to change.

3766471 -EN-DKK | 10.2024