

Informacje o produktach

Mechaniczny czujnik zegarowy MarCator 29I

Właściwości produktu

- Unit construction and removable movement save repair/cleaning time and maintenance
- Hardened gears and stainless steel racks provide lasting protection against indicator failure due to shock or wear
- Jeweled bearings resist friction, add to longer indicator life
- Skeletonized, hobbled gears for more sensitive response, superior indicator accuracy with minimal hysteresis error
- Soft tinted dials (green - inch / yellow - metric) minimize eye strain
- Special steel alloy
- Balanced dial hand affords no shift, precise reading
- Controlled rack and pinion mesh eliminates slope for precise response and reading
- Smooth adjusting bezels for easy setup
- Positive pressure pullback spring requires less maintenance
- Normally furnished: continuous clockwise dial; centered vertical lug back; regular contact point, .18" radiused, .250" long
- Long Range Models: include (1) revolution counter (except C9I without revolution counter). Extra Long Range Models: include (2) revolution counters
- For other dial styles or special requirements - call Mahr



Nr art.: **2014816**

Dane techniczne

Zakres pomiarowy w calach	1 inch
----------------------------------	--------

Wymiary

Wymiar B w calach (tekst)	1.625"
Wymiar A w calach (tekst)	2.25"
Wymiar D w calach (tekst)	.625"
Wymiar C w calach (tekst)	1.5"
Wymiar E w calach (tekst)	???