

Informações de produtos

Relógio comparador mecânico MarCator 12I-RC

Propriedades do produto

- Unit construction and removable movement save repair/cleaning time and maintenance
- Hardened gears and stainless steel racks provide lasting protection against indicator failure due to shock or wear
- Jeweled bearings resist friction, add to longer indicator life
- Skeletonized, hobbed gears for more sensitive response, superior indicator accuracy with minimal hysteresis error
- Soft tinted dials (green - inch / yellow - metric) minimize eye strain
- Special steel alloy
- Balanced dial hand affords no shift, precise reading
- Controlled rack and pinion mesh eliminates slope for precise response and reading
- Smooth adjusting bezels for easy setup
- Positive pressure pull back spring requires less maintenance
- Compliance with ANSI/AGD dimensional and accuracy specifications
- These indicators are normally furnished with continuous dial (with R.C.) or + on right balance dial (w/o R.C.), lug back and .18" by .250" long contact
- Optional Dials: balanced dial with + on left; continuous clockwise; continuous counterclockwise (Order by part number and specify dial style desired)
- For other dial styles or special requirements - call Mahr



Artigo nº: **2011001**

Dados técnicos

Intervalo de medição em polegada	0.03
---	------

Dimensões

Dimensão B em polegada (texto)	1,625"
Dimensão A em polegada (texto)	1.688"
Dimensão D em polegadas (texto)	,625"
Dimensão C em polegadas (texto)	1,5"
Dimensão E em polegadas (texto)	,344"

