

Информация об изделии

Калибровочные измерительные приборы Precimar ULM 1500 L-E

Комплект поставки

Standard software 828 WIN "Free measuring", PC evaluation unit (without monitor), Magnetic holder for temperature probe, Support table, Pair of measuring brackets, immersion depth 14 mm, 2 parallel gage blocks 60/20, 2 quick clamps, 2 measuring heads with spherical zone, Setting gage 2, USB stick, Weights 0.25/0.5/1.0/2.0N, Hexagonal wrench, Screwdriver, Accessories package



Область применения

Калибруемые приборы:

- Гладкие калибры-пробки и калибры-кольца
- Установочные кольца
- Калибры-скобы
- Сферические меры и нутромеры
- Концевые меры длины
- Резьбовые калибры
- Конусные резьбовые калибры
- Шлицевые калибры
- Конусные калибры
- Индикаторы часового типа
- Измерительные головки
- 2-точечные индикаторные нутромеры
- Микрометры
- 2-точечные микрометрические нутромеры

№ детали: 5350264

Технические характеристики

Диапазон измерения наружных размеров [мм]	От 0 до 1620
Диапазон измерения внутренних размеров [мм]	От 0,5 до 1465
Диапазон прямых измерений [мм]	От 0 до 1115
Погрешность измерений MPE_{E1} (L в мм) [мкм]	$\leq (0,1+L/2000)$
Повторяемость [мкм]	$\leq 0,05$
Измерительное усилие [Н]	0,2; от 1,0 до 4,5; 11
Длина прибора [мм]	2300
Вес [кг]	325
Размеры устройства	2300 x 380 x 480