

Ürün bilgileri

Kalibrasyon ölçüm aletleri Precimar ULM 1000-E

Ambalaj içeriği

Standard software 828 WIN
"Free measuring", PC evaluation unit (without monitor), Magnetic holder for temperature probe, Pair of measuring brackets, immersion depth 14 mm, 2 parallel gage blocks 60/20, 2 quick clamps, 2 measuring heads with spherical zone, Setting gage 2, USB stick, Weights 0.25/0.5/1.0/2.0N, Hexagonal wrench, Screwdriver, Accessories package



Uygulama

Kalibrasyon:

- Düz delik masterları ve master halkaları
- Ayar masterı halkaları
- Tutma masterları
- Küresel master blokları, dahili mikrometreler
- Master blokları
- Dişli masterlar
- Konik dişli masterlar
- Dişli masterlar
- Konik masterlar
- Analog indikatörler
- Analog komparatörler
- 2 noktalı delik masterlar
- Dış mikrometreler
- 2 noktalı iç mikrometreler
- Hassas tabla üzerinde uzunluk ölçümü

Malzeme no.: 5350262

Teknik veriler

Dış ölçüm için ölçüm aralığı [mm]	0 - 1060
İç ölçüm için ölçüm aralığı [mm]	0,5 - 905
Doğrudan ölçüm aralığı [mm]	100
Ölçüm belirsizliği MPE_{E1} (mm cinsinden L) [μm]	$\leq (0,09+L/2000)$ veya $\leq (0,3+L/1500)$
Tekrarlanabilirlik [μm]	$\leq 0,05$
Ölçüm kuvvetleri [N]	0,2 ; 1,0 - 4,5 ; 11
Aygıtın uzunluğu [mm]	1500
Kütle [kg]	215
Cihaz boyutları	1080 / 1500 / 2000 x 380 x 480 ULM 300-E: 685 x 280 x 480