


# Ürün bilgileri

## Kalibrasyon ölçüm aletleri Precimar ULM 1500-E

### Ambalaj içeriği

Standard software 828 WIN  
"Free measuring", PC evaluation unit (without monitor), Magnetic holder for temperature probe, Pair of measuring brackets, immersion depth 14 mm, 2 parallel gage blocks 60/20, 2 quick clamps, 2 measuring heads with spherical zone, Setting gage 2, USB stick, Weights 0.25/0.5/1.0/2.0N, Hexagonal wrench, Screwdriver, Accessories package



### Uygulama

Kalibrasyon:

- Düz delik masterları ve master halkaları
- Ayar masterı halkaları
- Tutma masterları
- Küresel master blokları, dahili mikrometreler
- Master blokları
- Dişli masterlar
- Konik dişli masterlar
- Dişli masterlar
- Konik masterlar
- Analog indikatörler
- Analog komparatörler
- 2 noktalı delik masterlar
- Dış mikrometreler
- 2 noktalı iç mikrometreler
- Hassas tabla üzerinde uzunluk ölçümü

Malzeme no.: 5350266

### Teknik veriler

<b>Dış ölçüm için ölçüm aralığı [mm]</b>	0 - 1560
<b>İç ölçüm için ölçüm aralığı [mm]</b>	0,5 - 1405
<b>Doğrudan ölçüm aralığı [mm]</b>	100
<b>Ölçüm belirsizliği <math>MPE_{E1}</math> (mm cinsinden L) [<math>\mu</math>m]</b>	$\leq (0,09+L/2000)$ veya $\leq (0,3+L/1500)$
<b>Tekrarlanabilirlik [<math>\mu</math>m]</b>	$\leq 0,05$
<b>Ölçüm kuvvetleri [N]</b>	0,2 ; 1,0 - 4,5 ; 11
<b>Aygıtın uzunluğu [mm]</b>	2000
<b>Kütle [kg]</b>	280
<b>Cihaz boyutları</b>	1080 / 1500 / 2000 x 380 x 480 ULM 300-E: 685 x 280 x 480